



Produs omologat de COMANDAMENTUL POMPIERILOR
Product approved by ROMANIAN FIREMEN COMMITTEE

POZ. ITEM	REPER / PART NAME	MATERIAL / MATERIAL	
		TIP / TYPE	SIMBOL / SYMBOL
1	Cutie obturator Obturator box	fonta cenusie cast iron	EN-GJL-250
2	Obturator Obturator	cauciuc rubber	EPDM
3	Inel Ring	aliaj Cu copper alloy	-
		fonta cenusie cast iron	EN-GJL-250
4	Corp obturator Obturator body	fonta cenusie cast iron	EN-GJL-250
5	Teava de legatura Connecting pipe	otel carbon carbon steel	-
6	Corp subteran Underground body	fonta cenusie cast iron	EN-GJL-250
7	Corp superior Upper body	fonta cenusie cast iron	EN-GJL-250
8	Racord infundat Blocked connection	aluminiu aluminium	-
9	Tija Stem	inox cu min. 11,5% Cr 11,5%Cr stainless steel	-
10	Piulita tije Stem nut	aliaj Cu copper alloy	-
11	Capac II Bonnet II	fonta cenusie cast iron	EN-GJL-250
12	Capac I Bonnet I	fonta cenusie cast iron	EN-GJL-250
13	Capac superior manevra Operational upper bonnet	fonta cenusie cast iron	EN-GJL-250
		Garnituri Gaskets	cauciuc rubber
	Organe de asamblare Bolting	otel carbon carbon steel	-

CARACTERISTICI CONSTRUCTIVE / DESIGN CHARACTERISTICS:

- constructie / design: STAS 3479;
- adancimi de ingropare / burying depths: 1,25m ; 1,5m ;
- flanse de legatura / connection flanges: PN10 EN 1092-2 ; ISO 7005-2 ; DIN 2501 ;
- viteza de curgere / flow speed: 3m/s ;
- etansare tija / stem sealing: inele O / O ring ;

(dimensiuni in mm / dimensions in mm)

DN	DE PEHD	H	H1	H2	d1	d2	nxd3	Racorduri / Connectors			Masa neta / Net weight (≈ kg)
								Nr. buc./ Quantity	Tip / Type	Dimensiuni Dimensions (inch)	
80	75	2390	1250	2120	200	160	8x19	2	C	2"	126
	95	2630	1500	2360				1	A	4"	135
100	110	2450	1250	2120	220	180	8x19	2	B	2 1/2"	129
	125	2690	1500	2360				1	A	4"	138

Pentru confirmare va rugam folositi fisa tehnica contractuala / For confirmation, please use the technical sheet of agreement FTC15