



**CARACTERISTICI CONSTRUCTIVE / DESIGN CHARACTERISTICS:**

- constructie / design: SR ISO 10631
- lungimi de constructie / overall length:: EN 558-1 – S20; ISO 5752 – S20
- flanse de legatura / connecting flanges : PN10; PN16 – EN 1092-2; ISO 7005-2; DIN 2501  
- cls.125/150-ANSI B16.1/ANSI B16.5
- viteza maxima de curgere / max. flow speed for liquids: – 3 m/s pentru / for PN 10 si / and 4m/s pentru / for PN 16

**TEMPERATURA MAXIMA/TEMPERATURA MINIMA DE LUCRU-TS:**

**MAX. / MIN. WORKING TEMPERATURE - TS:**

- 80°C/-10°C pentru / for NBR
- 120°C/-10°C pentru / for EPDM

(dimensiuni in mm / dimensions in mm)

DN	Tip levier Lever type	A	B	C	E	M	Masa neta Net weight ≈ [Kg]		Tip mecanism Gearbox type	A	B	C	G	M1	N	Dr	Moment actionare la roata Driving torque on wheel [daNm]	Masa neta Net weight ≈ [Kg]					
							Wafer	Lug										Wafer	Lug				
50*	LMC 220	180	107	30	62	220	3.2	4.1	RWA40-34	180	107	56	130	40	50	135	2,7	4.4	5.3				
65*		194	114.5				3.5	4.6		194	114.5							4.7	5.8				
80*		218	122				3.9	5.5		218	122							5.1	6.7				
100*		254	140				5.5	7.6		254	140							6.1	8.8				
125*	LMC 325	289	150	33	62	325	7.8	9.4	RWA40-34	289	150	60	165	50	55	215	3,5	8.2	10.3				
150*		315	174				9.6	14		315	174							10.6	15.1				
200*		LMC 430	390				208	39		430	15.5							23.6	RWA40-34	390	208	60	50
250	-	-	-	-	-	-	-	-	RW50-32	472	275	69	165	65	64	300	10,5	24.1	33.2				
300									543	310	34.4							46.5					
350									RW65-40	592	317							100	223	80	74.5	84.5	
400									RW90-58	665	350							110	266	100	12,8	117	129
500									RW120-64	768	400							130	270	130	20,5	172	187
600									RW120+RS105-218	890	460							130	406	261	11,2	281	304

\* RF PN 16

Pentru confirmare va rugam folositi fisa tehnica contractuala / For confirmation, please use the technical sheet of agreement FTC9